



BATTERY				
BATTERY VOLTAGE	±96/108/120VDC; BATTERY QUANTITY (16-20 PCS, 16 PCS DEFINE, STANDARD UNIT AND 20 PCS NO POWER DERATING; 18 PCS OUTPUT POWER FACTOR 0.8/0.9; 16 PCS OUTPUT POWER FACTOR 0.7/0.8;)			
CHARGING CURRENT (A)(CHARGING CURRENT CAN BE SET ACCORDING TO BATTERY CAPACITY INSTALLED)	14A (MAX.)	16A (MAX.)	18A (MAX.)	20A (MAX.)
SYSTEM FEATURES				
TRANSFER TIME	UTILITY TO BATTERY : 0MS; UTILITY TO BYPASS: 0MS			
OVERLOAD	≤110% OVERLOAD 60 MIN; ≤150% OVERLOAD 1 MIN; BYPASS MODE:135% OVERLOAD LONG TIME; >1000% OVERLOAD 100 MS			
BACKFEED PROTECTION	SUPPORT			
ALARM	OVERLOAD, UTILITY ABNORMAL, UPS FAULT, BATTERY LOW, ETC.			
PROTECTION	SHORT CIRCUIT, OVERLOAD, OVER TEMPERATURE, BATTERY LOW, FAN FAULT ALARM.			
REMOTE LCD	SUPPORT			
COMMUNICATION INTERFACE	USB, RS232, RS485, PARALLEL PORT, DRY CONTACT, INTELLIGENT SLOT, LBS, SNMP CARD (OPTIONAL), RELAY CARD (OPTIONAL)			
ENVIRONMENT				
OPERATING TEMPERATURE	0C~40C			
STORAGE TEMPERATURE	-25C~55C			
HUMIDITY RANGE	0F695% (NON-CONDENSING)			
ALTITUDE	<1500M. WHEN >1500M, DERATING POWER FOR USE			
NOISE LEVEL	<55DB	<55DB	<58DB	<61DB
PHYSICAL				
DIMENSION D×W×H (MM)	828×250×868			
NET WEIGHT (KG)	57	63	64	71
STANDARDS				
SAFETY	IEC/EN62040-1,IEC/EN60950-1			
EMC	IEC/EN62040-2,IEC61000-4-2,IEC61000-4-3,IEC61000-4-4,IEC61000-4-5,IEC61000-4-6,IEC61000-4-8			

