

UPS Techno PRO

1200VA – 1500VA – 2000VA

Line Interactive POWER SUPPLY TP Series UPS

1200VA > 2000VA

ALARM			
BATTERY LOW	SOUNDING EVERY SECOND		
OVERLOAD	SOUNDING EVERY 0.5 SECOND		
BATTERY REPLACEMENT ALARM	SOUNDING EVERY 2 SECONDS		
FAULT	CONTINUOUSLY SOUNDING		
Management			
USB & RS-232 PORT (OPTIONAL)	USB OR RS232(SUPPORTS WINDOWS ,LINUX, UNIX, AND MAC)		
LCD	UPS STATUS, INPUT/OUTPUT VOLTAGE, INPUT/OUTPUT FREQUENCY, LOAD LEVEL, BATTERY CAPACITY, AND WARNING OR FAULT ERROR CODE.		
PHYSICAL			
DIMENSION W X D×H (MM)	158×380×198	144×432.5×207	144×432.5×207
NET WEIGHT (KG)	10.5	20	22
ENVIRONMENT			
OPERATING TEMPERATURE	0C~40C		
HUMIDITY RANGE	20~95%RH @ 0~40C (NON CONDENSING)		
NOISE LEVEL	<45DB (1 METER FROM SURFACE)		
STANDARDS			
SAFETY	IEC/EN62040-1,IEC/EN62477-1		
EMC	IEC/EN62040-2,IEC61000-4-2,IEC61000-4-3,IEC61000-4-4,IEC61000-4-5,IEC61000-4-6,IEC61000-4-8		