








UPS Techno PRO

Line Interactive POWER SUPPLY TP Series
UPS 3000VA



230 VAC



SPECIFICATION

MODEL	TP3000LI		
CAPACITY	3000VA/1800W		
INPUT			
NOMINAL INPUT VOLTAGE	110/120VAC OR 220/230/240 VAC		
OPERATING VOLTAGE RANGE	81-145VAC/162-290 VAC		
OPERATING FREQUENCY RANGE	50/60 HZ (1±10%)		
OUTPUT			
OUTPUT VOLTAGE RANGE (BATT. MODE)	SIMULATED SINEWAVE AT NOMINAL VOLTAGE ±10%		
FREQUENCY RANGE (BATT. MODE)	50 HZ OR 60 HZ ± 1 HZ		
TRANSFER TIME	TYPICAL 2-6 MS, 10MS MAX.		
BATTERY			
BATTERY TYPE & NUMBER	12 V / 7.2 AH X 2	12 V / 9 AH X 2	12 V / 9 AH X 2
TYPICAL RECHARGE TIME	6-8 HOURS (TO 90% CAPACITY)		
PROTECTION			
TYPICAL RECHARGE TIME	OVERLOAD AND OVERCHARGE PROTECTION		
INDICATORS			
TYPICAL RECHARGE TIME	AC MODE, BATTERY MODE, LOAD LEVEL, BATTERY LEVEL		



UPS Techno PRO

Line Interactive POWER SUPPLY TP Series
UPS 3000VA

ALARM	
BATTERY MODE	SOUNDING EVERY 10 SECOND
BATTERY LOW	SOUNDING EVERY SECOND
OVERLOAD	SOUNDING EVERY 0.5 SECOND
BATTERY REPLACEMENT ALARM	SOUNDING EVERY 2 SECONDS
FAULT	CONTINUOUSLY SOUNDING
Management	
USB & RS-232 PORT (OPTIONAL)	USB OR RS232(SUPPORTS WINDOWS ,LINUX, UNIX, AND MAC)
LCD	UPS STATUS, INPUT/OUTPUT VOLTAGE, INPUT/OUTPUT FREQUENCY, LOAD LEVEL, BATTERY CAPACITY, AND WARNING OR FAULT ERROR CODE.
PHYSICAL	
DIMENSION W X D×H (MM)	158×380×198
NET WEIGHT (KG)	10.5
ENVIRONMENT	
OPERATING TEMPERATURE	0C~40C
HUMIDITY RANGE	20~95%RH @ 0~40C (NON CONDENSING)
NOISE LEVEL	<45DB (1 METER FROM SURFACE)
STANDARDS	
SAFETY	IEC/EN62040-1,IEC/EN62477-1
EMC	IEC/EN62040-2,IEC61000-4-2,IEC61000-4-3,IEC61000-4-4,IEC61000-4-5,IEC61000-4-6,IEC61000-4-8