









**UPS Techno PRO**

700VA – 900VA – 1000VA

Line Interactive POWER SUPPLY TP Series UPS

700VA > 1000VA



**230 VAC**



**SPECIFICATION**

MODEL	TP700LI	TP900LI	TP1000LI
CAPACITY	700VA / 360W	900VA / 480W	1000VA / 600W
<b>INPUT</b>			
NOMINAL INPUT VOLTAGE	110/120VAC OR 220/230/240 VAC		
OPERATING VOLTAGE RANGE	81-145VAC/162-290 VAC		
OPERATING FREQUENCY RANGE	50/60 HZ (1±10%)		
<b>OUTPUT</b>			
OUTPUT VOLTAGE RANGE (BATT. MODE)	SIMULATED SINEWAVE AT NOMINAL VOLTAGE ±10%		
FREQUENCY RANGE (BATT. MODE)	50 HZ OR 60 HZ ± 1 HZ		
TRANSFER TIME	TYPICAL 2-6 MS, 10MS MAX.		
<b>BATTERY</b>			
BATTERY TYPE & NUMBER	12 V / 7.2 AH X 1	12 V / 9 AH X 1	12 V / 7.2 AH X 2
TYPICAL RECHARGE TIME	6-8 HOURS ( TO 90% CAPACITY)		
<b>PROTECTION</b>			
TYPICAL RECHARGE TIME	OVERLOAD AND OVERCHARGE PROTECTION		
<b>INDICATORS</b>			
TYPICAL RECHARGE TIME	AC MODE, BATTERY MODE, LOAD LEVEL, BATTERY LEVEL		



## UPS Techno PRO

700VA – 900VA – 1200VA

Line Interactive POWER SUPPLY TP Series UPS

700VA > 1200VA

<b>ALARM</b>			
BATTERY MODE	SOUNDING EVERY 10 SECONDS		
BATTERY LOW	SOUNDING EVERY SECOND		
OVERLOAD	SOUNDING EVERY 0.5 SECOND		
BATTERY REPLACEMENT ALARM	SOUNDING EVERY 2 SECONDS		
FAULT	CONTINUOUSLY SOUNDING		
<b>Management</b>			
USB & RS-232 PORT (OPTIONAL)	USB OR RS232(SUPPORTS WINDOWS ,LINUX, UNIX, AND MAC)		
LCD	UPS STATUS, INPUT/OUTPUT VOLTAGE, INPUT/OUTPUT FREQUENCY, LOAD LEVEL, BATTERY CAPACITY, AND WARNING OR FAULT ERROR CODE.		
<b>PHYSICAL</b>			
DIMENSION W X D×H (MM)	101×298×142	149.3×338×162	149.3×338×162
NET WEIGHT (KG)	4.3	4.9	7.8
<b>ENVIRONMENT</b>			
OPERATING TEMPERATURE	0C~40C		
HUMIDITY RANGE	20~95%RH @ 0~40C (NON CONDENSING)		
NOISE LEVEL	<45DB (1 METER FROM SURFACE)		
<b>STANDARDS</b>			
SAFETY	IEC/EN62040-1,IEC/EN62477-1		
EMC	IEC/EN62040-2,IEC61000-4-2,IEC61000-4-3,IEC61000-4-4,IEC61000-4-5,IEC61000-4-6,IEC61000-4-8		